

Atrust

Thin Client Atrust t10W



1 Microphone Port

Connects to a microphone.

2 Headphone Port

Connects to a headphone or a speaker system.

3 USB 3.0 Port

Connects to a USB device.

4 USB 2.0 Port

Connects to a USB device.

5 Power LED

Indicates the status of power.

6 Power Button

Press to turn on/off the client.

7 DC IN

Connects to an AC adaptor.

8 LAN Port

Connects to a host server through a LAN switch.

9 USB 2.0 Port x 2

Connects to a USB device.

10 DVI-I Port

Connects to a monitor.

11 RS-232 Port

Connects to a serial port device.

12 Antenna (Manufacturing option)

Connects to a wireless network.

Atrust t10W Features

- ▶ Durable and quiet design
- ▶ Simplified management
- ▶ Compact and robust design
- ▶ Low power consumption
- ▶ Lower total cost of ownership (TCO)
- ▶ Supported Protocols
t10W supports the following protocols:
Citrix® ICA/HDX™, Microsoft® RDP™ with RemoteFX™, VMware® Horizon View™



Atrust t10W

System	t10W
Processor	Intel® Bay Trail Dual Core 1.58GHz
Memory	
System memory	2GB (Manufacturing option: 4GB)
Flash memory	8GB (Manufacturing option: 16GB, 32GB, 64GB)
Graphics	
Maximum resolution	Up to 1920 x 1200
I/O Interfaces	
I/O ports	Front: 1 x USB 3.0, 1 x USB 2.0, 1 x Microphone port, 1 x Headphone port, Rear: 1 x DVI-I, 2 x USB 2.0, 1 x RS-232 port, 1 x RJ-45, 1 x DC IN
Networking	
Ethernet	10/100/1000Mb
Dimensions / Weight	
Dimensions	(W) 155 x (D) 109.6 x (H) 37 mm
Weight	810g (approximate, with WiFi antenna)
Environment	
Cooling	Fanless
Operating noise	No noise
Operating temperature	-20°C ~ 55°C
Non-operating temperature	-40°C ~ 80°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Non-operating humidity (Rh)	5% ~ 95% (non-condensing)
AC Adaptor	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
Rated output current (max)	3A
Output voltage	+12V DC
Software	
Operating system	Windows® Embedded Standard 7 (WES7) Windows® Embedded 8 Standard (WE8S) Windows® 10 IoT Enterprise for Thin Clients * 16GB flash memory is the minimum requirement for Windows® 10 IoT Enterprise for Thin Clients
Management	Atrust Device Manager (ADM) / Atrust Client Setup (ACS)
Protocols	Citrix® ICA/HDX™, Microsoft® RDP™ with RemoteFX™, VMware® Horizon View™
Option	WiFi antenna TPM 2.0

© 2016 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Citrix and ICA/HDX are trademarks of Citrix Systems, Inc.. VMware and Horizon View are trademarks of VMware, Inc.. To learn more, visit www.atrustcorp.com.