



# CENTERM

## Centerm C33

Hardware

Specification		
Processor	CPU	Intel D2550 1.86GHz Dual-core
Memory	RAM	2GB DDR3 RAM (up to 4GB)
Storage	DOM	8G SATA DOM (could be extended hard disk)
I/O Peripheral Support	DVI-I	x1 ( Standard DVI to VGA adapter)
	USB 2.0	x6 ( Front x2, Rear x4)
	Serial port	x4 ( Blue serial extension cable)
	Parallel port	x1
	PS/2	x2
Networking	LAN	x1 (10/100/1000 Base-T Fast Ethernet, RJ-45)
	WLAN	- Optional USB 802.11b/g mini PCI-E wireless module Wake on LAN, PXE bootable
Display Support	Resolution	VGA: Up to 1920x1200@60Hz DVI: Up to 1920x1200@60Hz
	Color Depth	Up to 32bits true color
Audio	Line-out	- Output: 1/8-inch mini jack
	Mic-in	- Input: 1/8-inch mini jack
Physical Characteristics:	Dimension	204 X 55 X252 mm
	Gross Weight	3.22kg
	Net Weight	1.48kg
Mountings	Feet Stand	Vertical feet
Power	Adapter	12V/3A
	TDP	10W
	Full load power consumption	8.17W
	Desktop Power	11.42W
Environment	Operation Temperature	0°C - 40°C
	Relative Humidity	30% to 90% non-condensing

**Firmware Features**
**Software**

Centerm COS4.19

Citrix Receiver 12.1.2

CT Vision Client 5.20

RDP 1.6.0

Citrix ICA/HDX

RDP/VMware View PCoIP

RDP 5.2

Microsoft WES7 SP1

RDP 6.1.7601

Citrix Receiver 13.3










VMware View Client 5.1

RDP 7.1 (support RemoteFX)

Citrix ICA/HDX

RDP/VMware View PCoIP



No.	Name	Icon	
1	Power		
2	USB port		
3	Mic-in		
4	Line-out		
5	DC 12V input		
6	PS/2		
7	Serial		
8	DVI-I		
9	Parallel		
10	RJ-45	